

Accessories **HMI Covers**

SolarShield HMI Cover 20 x 14 Inch Clear Cover

Catalog Number HMICVR2014C
UPC 191564120836.0

List Price

\$477.76

Description

SolarShield HMI Cover 20 x 14 Inch Clear Cover by AttaBox®

SolarShield HMI Cover 20 x 14 Inch Clear Cover by AttaBox®

20W in x 14H Inch SolarShield HMI Clear Cover for HMI Devices offer the most innovative, durable non-metallic HMI Covers for use with all enclosure material types. The clear version has an easy to use, hinged design with clear cover which allows for visibility of the HMI screen while the cover is closed. SolarShield HMI Clear covers protect HMI screens and electrical equipment from corrosion and damage due to water, oils, dirt, and sand and greatly reduce equipment replacement cost. Impact resistant polycarbonate construction provides long dependable life in harsh conditions. The Clear Cover configuration allows for excellent visibility of the HMI screen while the cover is closed.

Application

Provide superior protection of Human Machine Interface (HMI) screens from wind-blown dust, and other environmental conditions

Features

- Clear Cover for visibility of HMI Display and Indicator Lights
- Fits most standard Size 15 and smaller HMI screens
- NEMA 4/4X rating
- Universal covers can be used with either non-metallic or metallic enclosures
- Lightweight, high-Impact rated, UV resistant polycarbonate

material construction

- Stainless steel hardware kit Included
- Padlock-able for increased security
- Simple and easy installation with the use of common tools
- Available as standalone SKUs or assembled to our enclosures with added HMI cutouts through our value-add ModRight program.
- Inner Doors not included

General Information

Color	Clear
Cover Type	Clear
Mounting Type	Box Mount
Material	Polycarbonate
Cover Screw Size	#10-32 x 5/11
Cover Screw Recommended Torque	20-24 in-lbs
Cover Screw Material	304 SS
Installation Mounting Torque	20-24 in-lbs Max
Hinge Material	Integral Polycarbonate
Latch Material	Nylon
Gasket Material	Poured In Place (PIP) Polyurethane Seamless
Country of Origin	India

Dimensions

Height (in)	18.0
Width (in)	23.1
Depth (in)	2.6
Height (mm)	457.0
Width (mm)	586.0
Depth (mm)	66.0
Inside Height (in)	14.3
Inside Width (in)	19.9
Inside Depth (in)	2.2

Standards

UL508A	cULus Listed File #E540056
Type	4; 4X
Temperature Range °F	-40°F to +248°F
Temperature Range °C	-40°C to +120°C
Flamability Rating	UL94-5VA
Outdoor Exposure UL746c	(f1) Rated