Enclosures BantamBox Series

# Polycarbonate Enclosure 5 x 5 x 4 Inches BantamBox Clear Cover

| | |
|---|---|
| **Catalog Number** | BBCC121211W |
| **UPC** | 191564105215.0 |

List Price

**$82.77**

## Description

5H x 5W x 4D Inches BantomBox Series polycarbonate enclosures feature flush sides making it a sought-after enclosure for OEM designs. Raised bosses accommodate back panel mounting and are sucessfully used for remote sensor mounting and small electronic controls in any environment. This conifiguration features a clear lift off cover with 4 cover screws.

## Application

Small; simple design ideal for OEMs in the electronics market; circuit boards and wiring applications

## Features

- Available in 2 cover options: 1. Opaque Cover; 2. Clear Polycarbonate Cover
- Multiple depths available in most sizes
- Resistant to harsh environments
- Flush sides for optimal fit
- Multiple molded in bosses for a variety of mounting solutions

## General Information

| | |
|---|---|
| **Color** | Gray |
| **Cover Type** | Clear |
| **Mounting Type** | Wall Mount |
| **Material** | Polycarbonate |
| **Back Panel Screw Size** | Plastite 48 #8 |
| **Back Panel Recommended Torque** | 12-16 in-lbs. |
| **Back Panel Screw Material** | 304 SS |
| **Cover Screw Material** | 304 SS |
| **Metal Inserts** | Brass |
| **Gasket Material** | Poured In Place (PIP) Polyurethane Seamless |
| **Country of Origin** | Germany |

## Dimensions

| | |
|---|---|
| **Height (in)** | 5.0 |
| **Width (in)** | 5.0 |
| **Depth (in)** | 4.0 |
| **Height (mm)** | 120.0 |
| **Width (mm)** | 120.0 |
| **Depth (mm)** | 110.0 |
| **Useable Depth (in)** | 1.7 |
| **Useable Depth (mm)** | 44.0 |

## Standards

| | |
|---|---|
| **NEMA 10250; UL 50; UL 50e; UL508A** | cULus Listed File #E64358 |
| **Type** | 1; 3R; 4; 4X; 12 |
| **IEC 60529** | IP66 |
| **IEC 60529** | cULus Listed File #E362920 |
| **Temperature Range °F** | -40°F to +212°F |
| **Temperature Range °C** | -40°C to +100°C |
| **Flammability Rating** | UL94-V2 |
| **Outdoor Exposure UL746c** | (f1) Rated |
| **CE** | Certified |